



# Marble Tek 100% Solids Epoxy A-6100

## Product Description

Americrete A-6100 Marble Tek Water Base Epoxy is a 100% Solids Epoxy used as a decorative flooring system. Its durability and ease of application make it ideal to apply. Americrete's 100% Solids Epoxy A-6100 is available in 17 colors. Americrete's A-6150 Activator is available in 8 colors.

## Coverage Rate

Americrete's 100% Solids Epoxy A-6100 will yield approximately 100 square feet per kit. Highlight colors will yield 200-400 square feet. Activators will yield coverage rate is 150 square feet per quart.

## Primary Uses

Americrete's 100% Solids Epoxy A-6100 has no odor and cleans up with zylene. It is abrasion resistant, maintains the color and may need additional sealers. It is resistant to most chemicals.

## Typical Applications

Americrete's 100% Solids Epoxy A-6100 is used to protect and serve as a unique, colored flooring system. It can also be used for clean floor areas, such as kitchen floors, garages, residential interior flooring, etc. Note: A porcupine roller can be used to remove air out of the product.

## Limitations

Not recommended for application below 28 degrees F. This product is not for immersion or exterior use, and not to be applied on wet or damp surfaces. Americrete Beads A-1402 can be added to the product to produce an anti-skid surface. When applying this product the applicator (and everyone in the immediate area) must wear protective clothing such as a filtered mask, gloves, boots, long sleeve shirt, long pants, and eye protection.

## Important Notice to Purchaser

Please see Important Notice to Purchaser in the front of this Specification Book.