

# 2-30D Super



## SPECIFICATIONS:

**Part Number:** 2-30DMKIII  
**Cleaning Path:** 30 in. (750mm)  
**Travel Speed:** Up to 92 ft/min.  
(28m/min)  
**Production Capacity<sup>†</sup>:** 9,000 sq.ft./hr.  
**Blast Motor:** 15/20 hp, 2 motors  
**Amperage:** 59.8 A  
**Total System Current:** 73.1 A  
**Voltage:** 460V, 3 $\phi$ , 60 Hz  
**Minimum Generator:** 60 kW  
**Dimensions:** L 75 in. x W 39 in. x 48 H in.  
**Weight:** 1,575 lb. (714kg)  
**Dust Collector:** 8-54DC

The Blastrac 2-30D Super is a powerhouse machine designed for the big jobs that require high productivity. The drive system with integrated brake is designed for ramps and inclines, making the 2-30D ideal for parking decks. A high-speed travel switch on the 2-30D helps ensure uniform surface preparation by allowing for quick repositioning after each pass, without resetting the travel speed.

Use this Blastrac Super system for industrial plant and warehouse floors, parking garages, ship decks, highway or bridge work, airport runways and other large jobs.

## FEATURES & BENEFITS:

- 30 inch cleaning path
- Recommended for light to medium removal
- Excellent for warehouse floors or thin mil coating applications
- High-speed travel switch helps ensure uniform profiling by allowing for quick repositioning for successive passes, without resetting travel speed
- Base elevates the machine for easier transport
- Heavy-duty 854 dust collector included with system
- Prepares up to 9,000 sq.ft/hr.
- 20 hp blast motor, 2 motors