



Traffic Coat™

Buffable Waterbased Floor Polish



Description:

TrafficCoat is the ultimate buffable acrylic floor polish for concrete, masonry and tile surfaces. This product provides an extremely durable high-speed buffable finish with outstanding high gloss on application. **TrafficCoat** can be used in high traffic areas such as retail stores, hospitals and schools and instantly snaps back to an ultra high gloss through dry buffing or conventional spray buffing processes. **TrafficCoat** is a very effective finish coat, over White Mountain Crystal Seal, "Wet Look" Lacquer, Seal-Lock, or any other good quality concrete, tile or masonry sealer. **TrafficCoat** can be buffed or polished, has excellent slip resistance and offers an extremely hard finish against marring, scratching and scuffing. Can also be used on most conventional vinyl and linoleum type floors

For Use On:

- Troweled, colored or stamped concrete
- Natural and manufactured stone
- Conventional vinyl floors
- Concrete paver tiles
- Sealed Flagstone
- Unglazed tile
- Glazed tile
- Fired brick
- Terrazzo

Features:

- Buffable
- High gloss
- Mar resistant
- Slip resistant
- Scuff tolerant
- Scratch resistant

Limitations:

Not recommended for exterior use. Surface can be slippery when wet.

Specifications:

VOC: [as packaged] 200 g/l – (1.67 lbs./gal.)

WEIGHT PER GALLON: [average] 8.6 lbs.

FLASH POINT: [setaflash] >240°F

APPEARANCE:

ODOR: Mild

PACKAGE VISCOSITY: 18 sec. Zahn Cup #2

SOLIDS: [average]

By Weight 18 ± .5%

By Volume 16 ± .5%

COVERAGE: [average] 400 – 1000 sq.ft./gal

[For exact coverage rates, a measured quantity to proper saturation over a known area will provide a square foot coverage rate for a specific job.]

DRY SCHEDULE: [at 50% RH and 1.75 mils DFT]

	45° F.	60° F.	75° F.	90° F.
<i>Dry to Touch</i>	3 hrs	2 hrs	1 hrs	½ hr

ORDER CODE: W1-05

PACKAGING: [average]

8 -1 quart plastic jugs per case 16 lbs.

4 -1 gallon plastic jugs per case 40 lbs.

1 - 5 gallon pail 50 lbs.

SHIPPING DESCRIPTION: [CFR 49]

Ground/Air/Vessel: Not Regulated

UNIFORM FIRE CODE: [CFR 29] Non combustible

STORAGE TEMPERATURE: 35° F. - 120° F.

Keep Water Base Products From Freezing!

SHELF LIFE: [warranted] 1 Year

"HMIS" RATINGS: H - 1; F - 0; R - 0; PP - H



Traffic Coat™ : Buffable Waterbased Floor Polish

IMPORTANT NOTE: Before use on a job, thoroughly test this product on a sample to assure performance and appearance.

Preparation:

Surface must be completely clean and dry to the touch. Remove dirt, wax, old floor polish and defective coatings with White Mountain "Jobsite" cleaner or White Mountain "Stripper". After cleaning, allow surface to dry 24 hours prior to sealer application. Allow new concrete to cure for at least 14 days before application. For porous surfaces first apply White Mountain Crystal Seal to protect against floor staining and to prevent polish from penetrating the substrate.

Application:

Always test a small area to assure satisfaction of appearance. Apply **TrafficCoat** with a wax applicator, sponge mop or clean cloth. Apply a light even coat (do not allow to puddle). Allow at least 40 minutes drying time before walking on surface or applying an additional coat. Two or more light applications are recommended to start. Additional coats offer added gloss and protection.

THINNING: Is not required.

IMPORTANT NOTE: Over application and excess floor polish should not be allowed to pool or puddle. Wipe up any pools after 15 minutes.

MAINTENANCE: Clean floor with water and if necessary using a mild detergent. Do not use ammonia, ammoniated cleaners, or abrasives. Periodic buffing or a light reapplication may be needed in high traffic areas or where scratches have occurred.

CLEAN UP: When wet, flush with clean water

REMOVAL- REAPPLICATION: When removal is necessary use White Mountain "Jobsite" cleaner. Total removal should not be necessary for 2 to 5 years. Reapply as per application instructions.

Safety Information:

CAUTION: LIQUID CONTACT WITH EYE AND SKIN CAUSES IRRITATION. DO NOT INGEST. Contains propylene glycol monobutyl ether, CAS # 5131-66-8. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations.

FIRST AID: Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin wash thoroughly with soap and water. If swallowed get medical attention immediately. DO NOT induce vomiting.

KEEP THIS PRODUCT OUT OF THE REACH OF CHILDREN.

(09/10/03)

WARRANTY: The statements made herein, on labels, product bulletins, or by any of Triangle Coatings', Inc. employees or agents concerning this product are given for general information only. Due to variables beyond Triangle's control in application, surface preparation, surface temperature, humidity and other variable factors Triangle assumes no liability for any claim that may arise out of the use of its products and disclaims any warranty expressed or implied relating to the storage, application, thinning, merchantability, Buyer's assumption of performance, and the fitness for a particular purpose. Receipt of products from Triangle or its agents constitutes acceptance of the terms of this warranty. In the event that Triangle finds that the product delivered is not of Triangle's standard quality, Triangle will at its sole discretion, either replace the product or refund the purchase price. Triangle's choice of one of these remedies shall be the Buyer's sole remedy. Triangle will under no circumstances be liable for consequential damages, except insofar as liability is mandated by law. Triangle will deliver products at agreed times insofar as it is reasonably able to do so, but it will not be liable for failure to deliver on time when the failure is beyond its reasonable control.