3 Contributes LEED Points

ProSpec®

LEVEL SET PRIMER

Description

ProSpec® Level Set Primer is a liquid polymer latex designed as a bonding agent for interior applications of the Level Set self leveling products. All Level Set products must be used in conjunction with a Level Set Primer.

Features

- Bonding agent
- Concentrated re-emulsifiable adhesive

Uses

- Designed to enhance the properties of Level Set products providing maximum adhesion and seal between the substrate and the leveler
- For use over concrete and gypsum substrates

Technical Data

Density	Drying Time
8.9 lbs./gallon	2-4 Hours at 70º F (21º C)
Flash Point	**Additional Information:**
None	Water-based
	VOC compliant

Preparation

All substrates must be clean and primed before Level Set products are applied. Surfaces must be solid, completely clean, free of oil, wax, grease, sealers, curing compounds, asphalt, paint, dirt, loose surface material and any contaminants that act as a bond breaker. Weak concrete surfaces must be cleaned down to solid sound concrete by mechanical means. Acid etching or chemical cleaning is not acceptable. Remove all dust by vacuuming.

Mixing

Combine one gallon of Level Set Primer with one gallon of clean potable water. This mix will cover approximately 350-400 ft^2 (33-37 m^2) of floor area. The primer must be applied evenly with a nylon push broom having exploded tips. Do not use paint rollers, mops or spray equipment. Apply a thin primer layer leaving no bare spots, puddles or excess primer. Allow to dry to a clear, thin film (usually between 2-4 hours).

Very absorbent concrete, such as abraded floors, may require two applications of Level Set Primer thereby avoiding the development of bubbles and pinholes in the Level Set Product. Apply the first coat of Primer diluted with 3 parts water, apply, let completely dry and install a second coat mixed 1:1 with water. Let dry then apply the Level Set product.

For non-absorbent, non-porous subfloors such as cutback adhesive, wood, metal, ceramic tile, terrazzo etc. use ProSpec Level Set Primer Plus.

Clean Up

Clean equipment with water and detergent immediately after use.

LEVEL SET PRIMER

Best Performance

- DO NOT ALLOW TO FREEZE. Store above 40º F (4º C).
- Do not use below 40º F (4º C).
- Low temperatures and/or high humidity will extend drying time.
- For internal use only.
- Always install a test area, insuring suitability for intended use.

Coverage

Approximately 350-400 ft^2 (33-37 m^2) per diluted gallon.

Packaging

1 gallon (3.8 L) / 4 per case (38 lbs. (17 kg))
5 gallon (18.9 L) pails (48 lbs. (22 kg))

Storage

Always keep in warm dry place. Do not allow to freeze. Always tightly reseal container.

Shelf Life

One year when stored properly in original unopened container.

Caution

KEEP OUT OF REACH OF CHILDREN AND ANIMALS. WARNING!

Provide proper air circulation Can be irritating to eyes and skin. Avoid contact with eyes or prolonged skin contact. In case of eye contact, flush thoroughly with water, DO NOT RUB EYES and call physician immediately. Wash hands with soap and water. Do not take internally

Consult Material Safety Data Sheet for further information

First Aid

Inhalation: Remove to fresh air

Eye Contact: Irrigate eye with water or consult physician if irritation persists.

Skin Contact: Washed exposed skin area with soap and water; consult a physician if irritation persists.

Ingestion: Immediately consult a physician.

LIMITED 1 YEAR WARRANTY FROM DATE OF MANUFACTURE: Bonsal American warrants that this product and the materials used therein meet or exceed the applicable standards listed and enforced at the time of manufacture. Bonsal American will replace any product or part which proves defective due to quality of ingredients used or due to the manufacturing process itself. This Warranty shall apply only if the product is used in strict accordance with applicable specifications and instructions provided by Bonsal American for its use, and Bonsal American shall not be liable otherwise. Replacement of any defective product, or, at Bonsal Americans option, refund of the purchase of any defective product shall be the buyer's sole remedy under this Warranty, and Bonsal American shall in no event be liable for any damages in excess of the purchase price of the defective product. BONSAL AMERICAN SHALL IN NO EVENT BE LIABLE FOR ANY CONSEQUENTIAL, INCIDENTAL OR SPECIAL DAMAGES INCLUDING LOSS OF PROFITS OF ANY KIND. Product demonstrations are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. This Warranty constitutes the sole warranty given by Bonsal American in connection with this product. No modification of this Warranty in favor of any buyer shall be valid unless given in writing and signed by an officer of Bonsal American. Bonsal American has authorized no person to make or give any other warranties or representation, oral or written on its behalf. IN PARTICULAR, THERE ARE NO IMPLIED WARRANTIES, INCLUDING WITHOUT EXCEPTION WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

ProSpec® is the registered trademark of Bonsal American, Inc.
8201 Arrowridge Blvd. Charlotte, NC 28273 • www.prospec.com • E-Mail: prospec@oldcastleapg.com